

Green Digital Power-Tech CO., LTD.

Email: sales@green-charger.com Website: http://www.green-charger.com/

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	2/26/2014 5:12:00 PM			
COMMON/UNITE	DOC. NO:		REV.: 1.0	PAGE: 1 OF 2

BG1-A12 Battery Fuel Gauge Indicator Specification

No.	Item	Unit	Specification	Remark
<i>Specification</i>				
01	Rating Input Voltage	V	12V	BG1-A12 for 12V lead-acid battery
02	Suitable battery type	V	12V Lead- Acid	
03	Rating Input current	mA	10	
04	Power-off leakage current	mA	<0.5	Auto Power-off after 30 minutes
<i>Fuel Gauge</i>				
05	LED1 flashing light LED2~5 off		10% full capacity	This gauge is designed for discharge and idle condition usage. It is not recommended for charging condition. (If you want to know the charged power, please remove the charger and wait 3~5 minutes)
06	LED1 solid light LED2~5 off		20% full capacity	
07	LED1 solid, LED2 flashing LED3~5 off		30% full capacity	
08	LED1~2 solid light LED3~5 off		40% full capacity	
09	LED1~2 solid, LED3 flashing LED4~5 off		50% full capacity	
10	LED1~3 solid light LED4~5 off		60% full capacity	
11	LED1~3 solid, LED4 flashing LED5 off		70% full capacity	
12	LED1~4 solid light LED5 off		80% full capacity	
13	LED1~4 solid, LED5 flashing		90% full capacity	
14	LED1~5 solid		100% full capacity	
<i>Environment</i>				
15	Operate temperature	℃	-10~+50	Full load & natural convection.
16	Operate humidity	%RH	<+90	Relative humidity, non-condensing.
17	Storage temperature	℃	-40~+70	
18	Storage humidity	%RH	0~+95	Relative humidity, non-condensing.
19	Cooling	-	Natural convection	
20	Temperature factor	%	-	
21	Vibration resistance	-	5MM/50HZ/600S	Non-operating condition.
22	Impact resistance	-	1 meter drop test>=3 times	Non-operating condition.
<i>Mechanical</i>				
23	Weight	g	~10	
24	Size	mm	42 x 22 x 9	
25	Cable/Connectors	-	0.5m, AWG22, 2 wires	Red V+; Black V -
26	ESD	kV	2.0	

Green Digital Power-Tech CO., LTD.

Email: sales@green-charger.com Website: http://www.green-charger.com/

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	2/26/2014 5:12:00 PM			
COMMON/UNITE	DOC. NO:		REV.: 1.0	PAGE: 2 OF 2

BGI-A6 Top view



To battery "-" Negative
(Black wire)

To battery "+" Positive
(Red wire)

Push this button for "ON" working.
The LEDs display will auto power-off after 30 minutes.