





**L100-48 (58.8V 1.5A) 14S Li-ion Battery Charger**

Item	Specification	Remark
1.Input		
Rating input voltage	100~240Vac 50/60Hz	
Input voltage range	90~264Vac	
Rating input current	1.5Arms	Input:100V Output:Full load
Max input power	100W	Input:100V Output:Full load
2.Output		
No load output voltage	DC58.8V	
Output voltage range	DC35~58.8V	
Suit with battery type	14S Li-ion battery	
Charging current	1.5A \pm 10%	
Charging voltage	DC58.8V \pm 0.7V	
Charge-end current	\leq 0.13A \pm 0.03A	
Timer	-	
Max output power	88.2W	
Ripple voltage	\leq 588mV	Full load
Charging LED	Red:Charging	
	Green:Full charge or idle	
Shorted	Yes	
Reversed	Yes	
Efficiency	\geq 87%	Full load @220V
3.Environment		
Operate temperature	-10 ~ +40°C	
Operate humidity	< +90%	Relative humidity
Storage temperature	-40 ~ +70°C	
Storage humidity	0 ~ +95%	Relative humidity
Cooling	Natural	
Vibration resistance	5MM/50HZ/600S	Non-operating condition
Impact resistance	1 meter drop test 3 times	Non-operating condition
4.Mechanical		
Weight	400g	
Size	170X70X41MM	Casing only
Connector	Refer to order	
5.Safety		
Max. temperature rise	< 40°C on casing	
Safety approval	CE/cTUVus/CCC	
MTBF	30000H	
ESD	8.0KV	
Hi-Pot Insulation	i/p to o/p: 3000V (1 min)	

CU	STOMERE	VRE	V	ZONE	DE	SCRIPTION	CHA	BY/DATE	APP	BY/DATE
----	---------	-----	---	------	----	-----------	-----	---------	-----	---------



Shenzhen Green Digital Power-Tech CO.,LTD

TITLE:		L100W		MATT:	
MODEL:				WEIGHT:	
DES BY:		CAD FILE:		TEXTURE	
CHECK BY:		COLOR:		Paper Size: A4	
APP BY:		FIN SH/ TREATME NT:		SCALE: FT	
CUSTOMER P/N:				DATE:	