







G300-420070 (42.0V 7.0A) 10S Li-ion Battery Charger		
项目 Item	规格 Specification	备注 Remark
1.输入特性 Input		
额定输入电压 Rating input voltage	100~240Vac 50/60Hz	
输入电压范围 Input voltage range	90~264Vac	
额定输入电流 Rating input current	3.3Arms	Input:100V Output:Full load
最大输入功率 Max input power	320W	Input:100V Output:Full load
2.输出特性 Output		
空载输出电压 No load output voltage	DC42.0V $\pm 1\%$	
输出电压范围 Output voltage range	DC25.0~42.0V	
适用电池 Suit with battery type	10S Li-ion battery	
恒定电流 Charging current	7.0A $\pm 7\%$	
恒定电压 Charging voltage	DC42.0V $\pm 1\%$	
预充电流 Pre-charge	1.4A $\pm 7\%$	电压 $\leq 30.0V$ 预充
充电结束电流 Charge-end current	$\leq 0.7A \pm 10\%$	
定时器 Timer	-	
最大输出功率 Max output power	294W	
纹波电压 Ripple voltage	$\leq 500mV$	满载 Full load
充电指示灯 Charging LED	红灯闪 Red LED flashing	2Hz Error
	绿灯闪 Green LED flashing	0.45Hz 空载 No battery; 0.83Hz $< 25\%$ Capacity; 1.25Hz $\geq 25\%$ Capacity; 1.66Hz $\geq 50\%$ Capacity; 2.5Hz $\geq 75\%$ Capacity;
	绿灯常亮 Green LED on	充满 Full
输出短路保护 Shorted	有 Yes	
输出反接保护 Reversed	有 Yes	
效率 Efficiency	$\geq 95\%$	满载 Full load @220V
3.环境要求 Environment		
工作温度 Operate temperature	$-10 \sim +40^{\circ}C$	
工作湿度 Operate humidity	$< +90\%$	相对湿度 Relative humidity
存储温度 Storage temperature	$-40 \sim +70^{\circ}C$	
存储湿度 Storage humidity	$0 \sim +95\%$	相对湿度 Relative humidity
冷却方式 Cooling	自然冷却 Natural	
抗振动 Vibration resistance	5MM/50HZ/600S	非运行状况 Non-operating condition
抗冲击 Impact resistance	1 meter drop test 3 times	非运行状况 Non-operating condition
4.结构 Mechanical		
重量 Weight	1.3Kg	
尺寸 Size	220X105X44MM	外壳尺寸 Casing only
接线端子 Connector	按客户要求制定 Refer to order	
5.安全特性 Safety		
最大温升 Max. temperature rise	$< 40^{\circ}C$ on casing	
安全认证 Safety approval	CB/CE/FCC	
平均无故障时间 MTBF	30000H	
静电等级 ESD	8.0KV	
隔离耐电压 Hi-Pot Insulation	i/p to o/p: 3000V (1 min)	

CUSTOMER REV/		REV	ZONE	DESCRIPTION	CHA BY/DATE	APP BY/DATE



深圳市谷润数字电源有限公司

TITLE: G300W充电器

MATL:

MODEL:

WEIGHT:

DES BY:

CAD FILE:

TEXTURE NO.

CHECK BY:

COLOR:

Paper Size:A4

SCALE: Fit

PART NO.:

APP BY:

FINISH/TREATMENT:

DATE:

DATE: